

TECHNICAL SPECIFICATION

At Gerbür we pride ourselves in the realism of our laminate flooring and the Verdi collection is the ultimate in realistic look and feel of a real hardwood floor. From the seamless patented Uniclic joining system to the eased edges of the planks, the realism is further enhanced by our match registered embossing on the surface which follows the graining of the plank to further enhance the realism. Finished in matt finish to imitate perfectly an oiled floor and to keep up with the increase in popularity of the oiled look for those discerning customers who don't want a high gloss shiny look, Verdi matt oiled finish is the floor of choice.



PATENTED TECHNOLOGY

PROPERTY	INFO
Dimensions	1217mm x 147 mm x 12 mm
Package	10 pieces per carton = 1.79 m ²
Production	Direct faced laminate flooring / melamine impregnated paper / core high-density fibreboard made using 50% FSC timber TT-COC-1943 certified by BM TRADA under license
Installation Method	Floating floor installation
Fixing Method	Unclick click system
Classification (BS EN 13329)	32: Heavy domestic use AC4: Medium commercial use
Warranty	20 Years Residential Warranty 10 Years Commercial Warranty

PRODUCT CHARACTERISTICS HDF-BASE

FACTOR	STANDARS	UNIT	NOMINAL VALUE
Formaldehyde content	EN 622-1	mg/100g	<8 (class E1)
24h swelling	EN 622-5	%	<17%
Bending strength	EN 622-5	N/mm ²	23
Internal bond	EN 622-5	N/mm ²	1
Moisture content	EN 622-1	%	4 to 11

PRODUCT CHARACTERISTICS OF LAMINATED FLOOR CORE-BOARDS CLASS: 32

FACTOR	STANDARS	UNIT	NOMINAL VALUE
Abrasion	EN 1332	REV	AC 4: IP 4,000
Impact resistance	EN 1332	N & mm	≥ IC 2
Stain resistance	EN 438.2.15	Scale*	Group 1&2:5 Group 3:4
Edge swelling	EN 13329	%	≤ 18

