

TECHNICAL SPECIFICATION




With its upmarket shine **Wagner** is definately the floor of connoisseur and those who like to make a statement. If a persons choice of flooring can say a lot of who they are, **Wagner** speaks volumes. With an industry leading top layer of Crystalbrite™ technology **Wagner** is on the lips of designers and home owners alike.

Wagner has a four sided bevel adding even more depth and realism to an already stunning floor. The ultimate laminate floor for those who want the look of high gloss flooring with minimum maintenance.

PROPERTY	INFO
Dimensions	808mm x 133mm x 12mm
Package	10 pieces per carton = 2.39 m ²
Production	Direct faced laminate flooring / melamine impregnated paper / core high-density fibreboard made using 50% FSC timber certified by BM TRADA under license, TT-COC-1943
Laying	Must be laid as floating floor
Classification(BSEN13329)	32 : Heavy domestic use AC4 : Medium commercial use
Warranty	20 Years Residential Warranty 10 Years Commercial Warranty



How Laminate Floors Work



PRODUCT CHARACTERISTICS HDF-BASE

FACTOR	STANDARS	UNIT	NOMINAL VALUE
Formaldehyde content	EN 622- 1	mg/100g	<8 (class E1)
24h swelling	EN 622- 5	%	<17%
Bending strength	EN 622- 5	N/mm ²	23
Internal bond	EN 622- 5	N/mm ²	1
Moisture content	EN 622- 1	%	4 to 11

PRODUCT CHARACTERISTICS OF LAMINATED FLOOR CORE-BOARDS CLASS: 32

FACTOR	STANDARS	UNIT	NOMINAL VALUE
Abrasion	EN 13329	REVS	AC 4: IP 4,000
Impact resistance	EN 13329	N & mm	≥ IC 2
Stain resistance	EN 438.2.15	Scale*	Group 1&2: 5 Group 3:4
Edge swelling	EN 13329	%	≤ 18