

# 100% WATERPROOF FLOORING

# AQUA-CLICK



## TECHNICAL SPECIFICATION



Thickness (mm)	4.00	
Wear Layer (mm)	0.3	
Utilization Class	 	
Coating	PU with DiamondShield™	
Embossing	Real Wood Texture	
Bevelled	V-grooved	
Fiberglass	yes	
Installation Method	Floating floor installation	
Plank Size	177.8mm x 1219.2mm	
Sqm Per Pack	2.1677	
Pallet Packing	151.741 / 70 packs	
Impact Sound Insulation	ISO 717-2	5 dB
Chemical Resistance	EN423	High Resistance
Residual Indentation	EN433	≤ 0.08mm
Dimensional Stability	EN434	≤ 0.08%
Colour Fastness to Light	EN20105-B02	≥ 6
Slip Resistance	DIN51130	R10
Water Resistance	EN13553	100% Waterproof
Abrasion Resistance	EN660-2	Group T
Antimicrobial Activity	ASTMG 21-96	Class 0
Fire Rating	EN ISO 9239-1	Bfl - S1
Warranty for Domestic use	15 Years	
Warranty for Commercial use	7 Years	



Visually and to the touch, it is almost impossible to tell that Gerbür Aqua-Click is not a real wooden floor due to its incredibly realistic wood grain surface. This means you can have the the effect of natural stylish real wood with none of the disadvantages. Manufactured from 100% virgin PVC, meaning it is not only visually stunning, it is also extremely durable and 100% waterproof. Installed as a floating floor, Aqua-click simply clicks together very quickly and easily using the patented Uniclick locking system, and at only 4mm overall thickness it is a perfect floor for renovations or to place over any flat and level subfloor.



With Diamondshield™ scratch resistant surface Gerbür Aqua-click LVT flooring has been crafted to withstand the toughest environments from a child's nursery to a busy hotel foyer. No stiletto heel marks or indentations like real wood or unsightly. That sought after real wood floor look can be expensive to install and costly to maintain.

Gerbür Aqua-click offers superb natural effect, incredible durability and excellent value for money. Design and function, welcome to Gerbür.