

TECHNICAL SPECIFICATION

Handel handscraped collection from Gerbur epitomises the latest laminate flooring technology married to timeless elegance. Handscraped and distressed looking floors are becoming a very popular choice in today's upscale homes and commercial properties. Although these floors are a newer trend, their background is deeply rooted in history.


Before today's modern sanding and planing methods. Hardwood floors were handscraped on site to make floors flat and even. Today's modern advancements in technology means that Handel hand scraped laminate is exactly that done by hand in our factory before the protective top layer is added.

This is done to preserve the time honoured process, adding texture and depth, resulting in a truly unique laminate floor.

PROPERTY	INFO
Dimensions	808 mm X 148 mm X 12 mm
Package	20 pieces per carton = 2 .39 m ²
Production	Direct faced laminate flooring / melamine impregnated paper / core high-density fibreboard made using 50% FSC timber certified by BM TRADA under license, TT-COC-1943
Laying	Must be layed as floating floor
Classification (BS EN 13329)	32: Heavy domestic use AC4: Medium commercial use
Warranty	20 Years Residential Warranty 10 Years Commercial Warranty



How Laminate Floors Work



PRODUCT CHARACTERISTICS HDF-BASE


FACTOR	STANDARS	UNIT	NOMINAL VALUE
Formaldehyde content	EN 622- 1	mg/100g	<8 (class E1)
24h swelling	EN 622- 5	%	<17%
Bending strength	EN 622- 5	N/mm ²	23
Internal bond	EN 622- 5	N/mm ²	1
Moisture content	EN 622- 1	%	4 to 11

PRODUCT CHARACTERISTICS OF LAMINATED FLOOR CORE-BOARDS CLASS:32

FACTOR	STANDARS	UNIT	NOMINAL VALUE
Abrasion	EN 13329	REVS	AC 4: IP 4,000
Impact resistance	EN 13329	N & mm	≥ IC 2
Stain resistance	EN 438.2.15	Scale*	Group 1& 2: 5 Group 3: 4
Edge swelling	EN 13329	%	≤ 18



ROTATE AND CLICK



HORIZONTAL INSERTION



MEDIUM COMMERCIAL