

HURRICANE - TDS



SPECIFICATIONS

Description	Nylon Carpet Tile
Construction	Tufted Textured Loop
Face Fiber	100% Nylon BCF Solution-dyed
Pile Height	4+/-0.3mm
Total Height	6.5+/-0.3mm
Pile Weight	450+/-5%g/m2
Gauge	1/12"
Primary Backing Cloth	Non-woven Polyester Spunbonded
Backing	PVC with Glass Fiber
Size	50 x 50 cm



TESTING

CRI Green Label Plus	GLP1879
Colorfastness to Light	AATCC 16-03
Colorfastness to Water	AATCC 107-02
Colorfastness to Cleaning	AATCC 138-00
Colorfastness to Crocking	AATCC 165-99
Stain Resistance	AATCC 175-03
Compression force deflection	ASTM D 3574
Smoke density (flaming)	ASTM E 662
Smoke density (non-flaming)	ASTM E 662
Loose laid	BS 4790-1987
Edge Ravel	ASTM D 7267
Surface Flammability	ASTM D 2859
Radiant Flux	ASTM E 648
Tuft bind	ASTM D 1335
AACHEN dimensional stability	ASTM D 7570
Electrostatic propensity AATCC 134	0.5kv
Accelerated soilin	ASTM D 6540
	Rating 5.0

PERFORMANCE

Wear Classification	Heavy commercial
Wear Warranty	10 Years

